



20ft 2-axle skeleton semi trailer with 19 inch Landing Gear

JUPITER® is a large-scale semi trailer and special vehicles manufacturer and supplier in China. We have been specialized in semi trailer and special vehicles for more than 38 years. Our 20ft 2-axle skeleton semi trailer with 19 inch Landing Gear have a good price and quality advantage and had already exported to the Asia, Africa and South America countries. We look forward to becoming your long-term partner in China.

Product Description

This JUPITER® 20ft 2-axle skeleton semi trailer is suitable for carrying ISO 20FT containers, which are mostly used in the port, pier and container yards. 20ft 2-axle skeleton semi trailer with BPW Axle is the best choice for the transportation and operation of 20ft container van box with high efficiency and economic return, we use famous brand parts on 20ft 2-axle skeleton semitrailer with JOST 2 inch King Pin, such as FUWA or BPW Brands Axle, JOST King Pin.so we recommend the end users or drivers to choose this 20ft 2-axle skeleton semi trailer with 19 inch Landing Gear and welcome to inquiry about our 20ft 2-axle skeleton semi trailer.

JUPITER 40FT 2-AXLE SKELETON SEMI

TRAILER Parameter (Specification)

Specification:		
Туре:	20FT 2 Axles Skeleton Trailer	
Model:	JPT9352TJZG	
Dimension:		
Length:	7,200mm	
Width:	2,480mm	
Height:	1,540mm	
Wheel Base:	4150+1310mm	



Fromo & C+	ruoturo:
Frame & St	
Main beam:	Material Q345B. Fabricated "H" beam height 500mm, Top flange thickness 12mm, Middle web thickness6mm, Bottom flange thickness 14mm
Side beam:	14# channel steel
Platform:	2.5mm thick diamond plate with supporting channel, 4 lines 40*30 shaped steel
Kingpin:	2'(50#), bolted in type
Twist lock:	04 sets twist locks
Welding standard:	All welding are to be done by qualified welder per applicable national standard
Painting:	Shot blast at Standard SA 2.5 prior to application of primer, polyurethane top coat. Total DFT not less than 100um
Running gear:	
Suspension:	mechanicalsuspension, heavy duty leaf spring 7 pcs-16mmx90mm, China
Axle:	Fuwa brand 2pcs*13 ton capacity, China
Brake system:	Dual line pneumatic brake, SAE hose and connector, without ABS
Brake chamber:	2 unitsT30/30 spring brakechambers, 2 units T30 brake chambers
Air tank:	40L,1pc, China
Tire:	11R22.5,8 pcs. China
Rim:	8.25*22.5 steel disc wheel, 10 holes ISO,8pcs. China
Landing gear:	Fuwa 28T two speed telescopic manual landing gear
Electrical	System:
Voltage:	24 Volt
Receptacle:	7 way socket SAE standard, China
Front marker lamp:	White
Side marker	White & Red



lamp:		
Rear lamp:	Red	
Turn signal lamp:	Amber	
Reflector:	Per customer requirement	
Wiring:	Electric cable protected by PVC conduit on main frame	
Accessories:		
Mud guard:	Steel mud guard	
Spare wheel carriers:	1 pc	
Tool box:	1 pc	
Note: All the details not mentioned above should comply with Chinese regulations. If any component or structure changed, the price shall be modified accordingly.		